Technical parameters for solid fuel local space heaters EU 2015/1186 of 24 April 2015

Model identifier(s): **Jøtul F 500 ECO**Indirect heating functionality: no
Direct heat output...(kW) 8,8
Indirect heat output...(kW): N.A

	Preferred	Other	Emissions from space heating at nom			at nom
Fuel	fuel (only	suitable	PM	OGC	СО	NOx
	one):	fuel(s):	(x) mg/Nm ³ (13% O ₂)			
Wood logs with moisture content ≤ 25%	Yes	No	10	55	1108	101
Compressed wood with moisture content < 12%	No	No				
Other woody biomass	No	No				
Non-woody biomass	No	No				
Anthracite and dry steam coal	No	No				
Hard coke	No	No				
Low temperature coke	No	No				
Bituminous coal	No	No				
Lignite briquettes	No	No				
Peat briquettes	No	No				
Blended fossil fuel briquettes	No	No				
Other fossil fuel	No	No				
Blended biomass and fossil fuel briquettes	No	No				
Other blend of biomass and solid fuel	No	No				

Characteristics when operating with the preferred fuel

Seasonal space heating energy efficiency η_s [%]: 72

Energy Efficiency Index (EEI): 108,9

Item	Symbol	Value		Item	Symbol	Value	Unit		
Heat output				Useful efficien	cy (NCV as recei	ved)			
Nominal heat output	P _{nom}	8,8	kW	Useful efficiency nominal heat output	at η _{th,nom}	82	%		
Minimum heat output (indicative)	P _{min}	N.A.	kW	Useful efficiency minimum heat output (indicative	$\eta_{th,min}$	N.A.	%		
Auxiliary electricity	consumption	on		Type of heat out	tput/room tempe	rature contro	select one)		
At nominal heat output	el _{max}	x,xxx	kW	single stage heat temperature con	•	[yes/no]	Yes		
At minimum heat output	el _{min}	x,xxx	kW		two or more manual stages, no room temperature control		No		
In standby mode	el _{sB}	x,xxx	kW	with mechanic th		[yes/no]	No		
			•	with electronic ro	oom temperature	[yes/no]	No		
				with electronic ro	•	[yes/no]	No		
				with electronic ro		[yes/no]	No		
				Other control options (multiple selections possible)					
				room temperatur presence detection		[yes/no]	No		
				room temperatur open window det		[yes/no]	No		
				with distance con	trol option	[yes/no]	No		
Permanent pilot	flame powe	er requirem	ent	Sign:					
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW	Espen Auensen, R&D manager					
Contact details	Name and	address of th	ne suppli	: Jøtul AS, P.O. box 1	411, 1602 Fredrik	stad, Norway			