

Assessment of Performance Report

n.1880-CPR-076-004-22

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this Assessment of Performance Report applies to the construction product

Trademark: MCZ	Trademark: MCZ
HIGH 12	HIGH 14
CLUB COMFORT AIR 12 M3	MUSA COMFORT AIR 14 UP! M3
CLUB COMFORT AIR 12 UP! M3	PHILO COMFORT AIR 14 M2*
MUSA COMFORT AIR 12 M3	PHILO COMFORT AIR 14 UP! M2*
MUSA COMFORT AIR 12 UP! M3	Trademark: RED
STREAM COMFORT AIR 12 M2*	LOTO MULTIAIR 14 S2
STREAM COMFORT AIR12 UP! M2*	
SUITE COMFORT AIR 12 M3	
SUITE COMFORT AIR 12 UP! M3	

*wall stove

residential space heating appliance fired by wood pellets without hot water supply

placed on the market under the name or trademark of

MCZ GROUP S.P.A
VIA LA CROCE 8,
33074 VIGONOV0 DI FONTANAFREDDA (PN)
ITALY

This Assessment of Performance Report attests that the performance of the above-mentioned construction product has been assessed in accordance with the harmonized standard

EN 14785:2006

under AVCP system 3 with regard to the essential characteristics listed in Annex 1.

This Assessment of Performance Report will remain applicable as long as neither the harmonized standard, the construction product, nor the AVCP methods are modified significantly.

November 30, 2022

Head of laboratory
dr.ssa Claudia Marcuzzi

ANNEX 1

HIGH 12

Essential characteristic	Performance	Basis for the assessment of performance
Reaction to fire	A1	declared by the manufacturer
Distance to combustible materials (minimum distance in mm)	Rear = 120- 20* Sides = 250 Floor = 0	
Risk of burning fuel falling out	Pass	
Emission of combustion products [ref. at 13% O ₂]:	at nominal heat output: CO [0,008 %] CO [98 mg/Nm ³] CO 67[mg/MJ] NOx [148 mg/Nm ³] NOx [99 mg/MJ] OGC [1 mg/Nm ³] OGC [1 mg/MJ] Particulate matter [14 mg/Nm ³] Particulate matter [9 mg/MJ] at reduced heat output: CO [0,014 %] CO [170 mg/Nm ³] CO [113 mg/MJ] NOx [98 mg/Nm ³] NOx [65 mg/MJ] OGC [1 mg/Nm ³] OGC [1 mg/MJ] Particulate matter [14 mg/Nm ³] Particulate matter [10 mg/MJ]	
Surface temperature	Pass	Test report n. 1880-CPR 076-001-22 declared by the manufacturer
Electrical safety	Pass	
Cleanability	Pass	
Thermal output: Heat output	[11,9kW] at nominal heat output [3,9 kW] at reduced heat output	Test report n. 1880-CPR-076-22 declared by the manufacturer
Efficiency	η[90,8%] nominal heat output η[93,5%] at reduced heat output:	
Flue gas temperature	T[193° C] nominal heat output T[86°C] at reduced heat output	

*wall stoves

HIGH 14

Essential characteristic	Performance	Basis for the assessment of performance
Reaction to fire	A1	declared by the manufacturer
Distance to combustible materials (minimum distance in mm)	Rear = 120 -20* Sides = 250 Floor = 0	Test report n. 1880-CPR 076-001-22 declared by the manufacturer
Risk of burning fuel falling out	Pass	
Emission of combustion products [ref. at 13% O ₂]:	at nominal heat output: CO [0,009%] CO [109 mg/Nm ³] CO [72 mg/MJ] NOx [150 mg/Nm ³] NOx [100 mg/MJ] OGC [1 mg/Nm ³] OGC [1 mg/MJ] Particulate matter [13 mg/Nm ³] Particulate matter [9 mg/MJ] at reduced heat output: CO [0,014 %] CO [170 mg/Nm ³] CO [113 mg/MJ] NOx [98 mg/Nm ³] NOx [65 mg/MJ] OGC [1 mg/Nm ³] OGC [1 mg/MJ] Particulate matter [14 mg/Nm ³] Particulate matter [10 mg/MJ]	
Surface temperature	Pass	declared by the manufacturer
Electrical safety	Pass	
Cleanability	Pass	
Thermal output: Heat output	[13,8 kW] at nominal heat output [3,9 kW] at reduced heat output	Test report n. 1880-CPR-076-22 declared by the manufacturer
Efficiency	η [90,5%] nominal heat output η [93,5%] at reduced heat output:	
Flue gas temperature	T[205°C] nominal heat output T[86°C] at reduced heat output	

*wall stoves