

Declaration of performance

DoP F602eco-CPR-280319

PRODUCT

Product Type: Roomhetaers fired by solid fuel

Type, batch or serial number: Jøtul F 602 ECO

Intended use: Roomheater burning solid fuel without water supply

Fuel Wood logs

MANUFACTURER

Name:

Adress:

Postboks 1411
1602 Fredrikstad, Norway

Telephone:

+47 69 35 90 00

Email:

Post@jotul.no

CHECKS

According to AVCP:

System 3

Notified body:

Danish Tecnological Institute

NB-No:

1235

Test report no:

Harmonized technical specification:

EN 13240:2003:AC:2006/A2:2004:AC:2007

SAFETY

Safety distance to combustible materials	Minimum distances [in mm]
	Rear = 300
	Sides = 500
	Front = 550
	Floor = 0
	Ceiling = 700
	Also see the installation instructions
Fire safety	Pass
Reaction to fire	A1
Risk of burning fuel falling out	Pass
Surface temperature	Pass
Electrical safety	NA
Release of dangerous substance	x
Cleanability	Pass
Maximum water operating pressure	-
Mechanical resistance (to carry a chimney/flue)	x

PERFORMANCE AND EMISSION

Essential characteristics	Performance
Emission of combustion products	Pass
со	[0,0906 %], 1132 mg/Nm ³
NOx	87 mg/Nm3
OGC	55 mg/Nm3
PM	25 mg/Nm3
Flue gas temperature at the measuring section at nominal	
heat output [in °C]	259
Flue gas outlet temperature at nominal heat output [in °C]	311
Thermal output	Pass
Nominal heat output	4,9 kW
Nominal space heat output	
Nominal water heat output	NA
Energy efficiency	η [81%]
Durability	x

Declaration:

The performance of the product is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Espen Løkkevig

R&D Manager

(Name and function)

Fredrikstad, June 2019

(Sianature)