



Declaration of Performance (DoP)

No. F 263 AT-CPR-20130822	
Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 263 AT Series (Jøtul F 263 AT, Jøtul F 263 S AT)
Intended use of the product:	Roomheater burning solid fuel without water supply
Name and Address of the manufacturer:	Jøtul AS Postboks 1411, 1602 Fredrikstad, Norway Tel.: +47 69 35 90 00 E-mail: post@jotul.no
AVCP: <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i>	System 3
Notified body:	RWE Power AG, Feuerstättenprüfstelle
NB-No:	1427
Test report no:	FSPS-Wa 2028-EN
Declared performance:	
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm Jøtul F 263 AT, Jøtul F 263 S AT Rear = 100 Sides = 350 Corner = 100 Front = 800 <i>See also the installation instructions</i>
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,044 %] NOx [124 mg/m ³] OGC [52 mgC/m ³] PM [20 mg/m ³]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [241°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	7 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	η [82%]

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

(Name and function)

Fredrikstad, August 22nd, 2013

(Place and date of issue)

Tom J. Berglind

(Signature)