DECLARATION OF PERFORMANCE (DOP)

	NO90066600 CPR-20140821	
1.	Product Type:	Freestanding stove Scan 66
2.	Type, batch or serial number:	Scan 66-2, Scan 66-3, Scan 66-4, Scan 66-5
3.	Intended use of the product:	Heat distribution/room heating Without hot water supply Fuel type: Wood
4.	Name and Address of the manufacturer:	Scan A/S Glassvænget 3-9 5492 Vissenbjerg
5.	Contact address:	No relevance
6.	AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3
7.	Notified body: Test report no:	DTI NB-No 1235 300-ELAB-2081-EN Rev. 1
8.	Declared performance	
	Harmonized technical specification	EN 13240
	Essential characteristics	Performance
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out	A1 Minimum distances in mm: Rear: 150 Sides: 300 Front: 850 NPD
	Emission of combustion products	CO [0,029 %] NOx [85 mg/Nm³] OGC [27 mg/Nm³] Dust [27 mg/Nm³]
	Surface temperature	Pass
	Electrical safety	-
	Cleanability	Pass
	Maximum water operating pressure	-
	Flue gas temperature at nominal heat output [EN]	T [302°C]
	Mechanical resistance (to carry a chimney/flue)	NPD
	Thermal output Normal heat output Room heating output Water heating output	5 kW
	Energy efficiency	ŋ[78 %]

DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Ole Hansen (R&D LAB)

Vissenbjerg, Juni 29, 2016
(Place and date of issue)





DECLARATION OF PERFORMANCE (DOP)

	NO90066601 CPR-20140821		
1.	Product Type:	Wall mounted stove SCAN 66	
2.	Type, batch or serial number:	Scan 66-1	
3.	Intended use of the product:	Heat distribution/room heating Without hot water supply Fuel type: Wood	
4.	Name and Address of the manufacturer:	Scan A/S Glassvænget 3-9 5492 Vissenbjerg	
5.	Contact address:	No relevance	
6.	AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3	
7.	Notified body: Test report no:	DTI NB-No 1235 300-ELAB-2081-EN Rev 1	
8.	Declared performance		
	Harmonized technical specification	EN 13240	
	Essential characteristics	Performance	
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out	A1 Minimum distances in mm: Sides: 300 Front: 850 Floor: 310 NPD	
	Emission of combustion products	CO [0,029 %] NOx [85 mg/Nm³] OGC [27 mg/Nm³] Dust [27 mg/Nm³]	
	Surface temperature	Pass	
	Electrical safety	-	
	Cleanability	Pass	
	Maximum water operating pressure	-	
	Flue gas temperature at nominal heat output [EN]	T[302°C]	
	Mechanical resistance (to carry a chimney/flue)	NPD	
	Thermal output Room heating output Water heating output	5 kW	
	Energy efficiency	ղ [78 %]	

DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Ole Hansen (R&D LAB)

Vissenbjerg, Juni 29, 2016
(Place and date of issue)



Ou Ham